

POD301RW

30-INCH SINGLE BUILT-IN OVEN

PROFESSIONAL SERIES, RIGHT SIDE OPENING DOOR



ALSO AVAILABLE:

POD301LW – Left Side Opening Door

FEATURES & BENEFITS

- Specially crafted gray glass on stainless steel for a luxurious look and finish
- Designed for flexibility – standard or flush installation into kitchen cabinets
- Ergonomically designed side opening door for better access to oven cavity
- Commercial style rotisserie with 12 pound capacity
- Multi-point Meat Probe to better capture temperature in roast and poultry
- Fast 2-hour self clean mode



GENERAL PROPERTIES

Heating Modes

(16) Bake, Broil, Max Broil, Roast, Convection Bake, Convection Broil, Max Convection Broil, Convection Roast, Proof, Warm, Pizza, True Convection, Dehydrate, Speed Convection, Slow Roast, Rotisserie

| | |
|------------------------------|-------------------------|
| Sabbath | Yes |
| Cleaning Type | Self Clean / Easy Clean |
| Telescopic Rack(s) | 3 |
| Illumination Type | Halogen |
| Interior Lights | 2 |
| Home Connect (Wi-Fi Enabled) | Yes |

OVEN PERFORMANCE

| | |
|--------------------|-------------------|
| Bake Element | 2,400 W |
| Broil Element | 3,800 W / 1,000 W |
| Convection Element | 2,000 W |

TECHNICAL DETAILS

| | |
|-----------------|---------------------------|
| Watts | 6,400 W |
| Circuit Breaker | 30 A |
| Volts | 240 / 208 V |
| Frequency | 60 Hz |
| Plug Type | Fixed Connection, No Plug |
| Conduit | 60" 4-Wire |
| Energy Source | Electric |

DIMENSIONS & WEIGHT

| | |
|--|-----------------------------------|
| Overall Appliance Dimensions (HxWxD) | 29" x 29 3/4" x 24 1/2" |
| Trim Overlaps (Top – Sides – Bottom) | 3/8" to 2" – 9/16" – 0" |
| Required Cutout Size (HxWxD) – Standard | 27" - 28 5/8" x 28 1/2" x 23 1/2" |
| Required Cutout Size (HxWxD) – Flush | 29 1/8" x 30 3/4" x 24 1/2" |
| Oven Cavity Size | 4.5 cu. ft. |
| Overall Oven Interior Dimensions (HxWxD) | 7 3/4" x 24" x 17 7/8" |
| Usable Oven Interior Dimensions (HxWxD) | 13 1/2" x 21 5/8" x 16 1/4" |
| Net Weight | 174 lbs |

ACCESSORIES (INCLUDED)

3 Telescopic Racks, Multi-point Meat Probe, Max Broil Pan, Rotisserie

WARRANTY

| | |
|----------------------------------|--------|
| Limited Warranty Parts and Labor | 2 Year |
|----------------------------------|--------|

ACCESSORIES (OPTIONAL)



SDCLNRCK30
30-Inch Oven Self-clean Standard Rack

POD301RW

30-INCH SINGLE BUILT-IN OVEN

PROFESSIONAL SERIES, RIGHT SIDE OPENING DOOR



INSTALLATION DETAILS

Single Oven Right Hinge

measurements in inches (mm)

Door Handle Depth*

Professional Series Side-Hinge Handle

*Protrusion of handle from door skin.

Single Oven Wall Mount Installation

measurements in inches (mm)

Dimensions for Under-Counter Installation

measurements in inches (mm)

- * Includes 3/4" (19 mm) base plate.
- ** For single ovens installed under a cabinet, the junction box should be located to the right or left of the unit within reach of the power cord.

Flush Install Top View

measurements in inches (mm)

Flush Install Side View

measurements in inches (mm)

POD301RW

30-INCH SINGLE BUILT-IN OVEN

PROFESSIONAL SERIES, RIGHT SIDE OPENING DOOR



INSTALLATION DETAILS

Standard installation
Single oven, double oven or combo oven over warming or storage drawer

- * Wall oven junction box may be located above or to the right or left of the unit within reach of the power cable.
- ** Electrical hook-up may be located below (depending on space) or next to the drawer within reach of the power cable.
- Minimum $\frac{3}{4}$ " (18 mm) required between cut-outs.

measurements in inches (mm)

Flush installation
Single oven over storage or warming drawer

Single wall oven

*IMPORTANT: Base has to be able to support the weight of the oven. Please check oven manual for minimum weight requirements.

minimum $\frac{1}{2}$ " (13 mm) required between cut-outs*

Warming drawer

**For WD30W, the installed dimension may differ. This drawing based on a $\frac{3}{4}$ " (19 mm) thick custom panel.

measurements in inches (mm)

Standard installation
30" speed oven or microwave above a single oven***

- * Junction box may be located above or next to the unit within the reach of the power cable.
- ** Junction box may be located below (depending on space) or next to the unit within the reach of the power cable.
- ***Most combinations available as combo oven (one cut-out, one electrical hook-up).

Minimum dimension between cut-out:

- 1" (25 mm) for wall oven cut-out height of $28\frac{5}{8}$ " (727 mm)
- $2\frac{5}{8}$ " (67 mm) for wall oven cut-out height of 27" (686 mm).

measurements in inches (mm)

Flush installation
Speed oven or microwave above a 30" single oven**

***Flush installation requires a base plate underneath the body: 30" products—Dimensions: H $\frac{5}{16}$ " (8 mm) x W $28\frac{1}{2}$ " (724 mm) x D $22\frac{1}{2}$ " (571 mm)

minimum $\frac{1}{2}$ " (13 mm) required between cut-out*

*IMPORTANT: Base has to be able to support the weight of the oven. Please check oven manual for minimum weight requirements.

**Most combinations available as combo oven (one cut-out, one electrical hook-up).

measurements in inches (mm)

POD301RW

30-INCH SINGLE BUILT-IN OVEN

PROFESSIONAL SERIES, RIGHT SIDE OPENING DOOR



INSTALLATION DETAILS

SIDE-BY-SIDE INSTALLATION – TOP VIEW

Standard

IMPORTANT: When installing an oven in combination, a minimum distance between the ovens is required. Refer to the oven installation manual for all other measurements.

measurements in inches (mm)

Flush

| Combination Type | A Left reveal cleat | B Right reveal cleat | C cut-out width | D cut-out width |
|--------------------------|---------------------------|----------------------------|-----------------------|-----------------------|
| Flush Bottom hinge | 3/4" (19 mm) | 3/4" (19 mm) | 29 1/4" (743 mm) | 29 1/4" (743 mm) |
| Flush Side Hinge (Left) | 1 1/2" (38 mm) | N/A* | 30" (762 mm) | N/A* |
| Flush Side Hinge (Right) | N/A* | 1 1/2" (38 mm) | N/A* | 30" (762 mm) |

*Installation not recommended

measurements in inches (mm)

These warranties give you specific legal rights and you may have other rights that vary from state to state. Full warranty and limited warranty from date of installation. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.