

Masterpiece® Series

48" Wall Hood

HMWN48FS



HMWN48FS Stainless steel

Performance

- 3 fan speeds plus 10 minute high-power operation mode
- Filter systems are highly efficient at capturing grease
- Powerfully quiet ventilation systems
- Extended capture area ensures removal of smoke and odor

Design

- Brushed stainless steel finish
- Welded, polished seams for a flawless design
- Premium electronic touch controls

Capacity

- 600 CFM Integrated Blower option VTN600F
- 1200 CFM Integrated Blower option VTN1000F
- Inline Blowers: VTI610D (600 CFM) or VTI1010D (1000 CFM)
- Remote Blowers: VTR630D (600CFM), VTR1030D (1000CFM), or VTR1330E (1300CFM)
- Remote Blower requires Roof Plate RFPLT600 for roof installations (600 CFM)
- Remote Blowers require Roof Plate RFPLT1000 for roof installations (1000/1300 CFM)
- 10" Round duct size
- Vertical ducting direction
- Recirculation possible with kit RECIRC__FS (max 600CFM)
- Replacement charcoal filters available (CHFILT3036)

Convenience

- Halogen lighting spotlights your best recipes
- Dishwasher safe low-profile baffle filters
- Grease collection trays are easily removed and dishwasher safe
- Built-in Clean Filter Reminder light
- Delayed shut off tackles lingering odors for up to 10 minutes
- Blowers sold separately
- Choose from Inline, Remote or Integrated Blowers
- Hood includes filters, lights, backdraft damper and transition

Optional accessories

PA48JBS 48" Backsplash Professional Line

RFPLT1000 Roof mounting plate for VTR1030D

RFPLT600 Roof mounting plate for VTR630D

825225863205

Masterpiece® Series

48" Wall Hood

HMWN48FS



Product Features

Operating Mode: Convertable: Ducted / Recirculating
Number of speed settings: 3-stage
Delay Shut off modes: 15
Optional accessories: DC48US, DCT48US, PA48JBS, RFPLT1000, RFPLT600
Number of lights: 3
Type of lamps used: Halogen
Total power of the lamps (W): 150
Grease filter material: Washable stainless steel
Grease filter type: Multilayer cassette
Clean filter reminders: Electronic

Consumption and connection features

UPC code: 825225863205
Material: Stainless steel
Watts (W): 150
Current (A): 15
Volts (V): 120
Frequency (Hz): 60
Approval certificates: CSA, UL
Power cord length (in):
Power cord length (cm):
Plug type: fixed connection
Overall appliance dimensions (HxWxD) (in): 11" / 11" x 48" x 23 1/8"
Overall appliance dimensions (HxWxD) (mm): 279 x 1219 x 587
Product packaging dimensions (HxWxD) (in): 23.99 x 12.99 x 49.38
Adjustable feet:
Height of the chimney (in):
Height of the chimney (mm):
Vertical rise height:
Required distance above cooktop/ranges: 30"/30"
Net weight (lbs): 30
Net weight (kg): 14.000
Gross weight (lbs): 48
Gross weight (kg): 22.000
Motor location:
Maximum CFM:
Diameter of air duct (in) top: 10
Diameter of air duct (in) back:
Discharge direction: vertical
No-return airflow flap: No

2013-07-12