HPIN48HS Professional Series 48" Island Hood



HPIN48HS Stainless steel

Performance

- · Three fan speeds
- · Filter systems are highly efficient at capturing grease
- · Powerfully quiet ventilation systems

Design

- · Brushed stainless steel finish
- · Chiseled design for a seamless integration into any kitchen
- · Stainless steel control buttons
- All-in-one low profile solution with the flexibility of having an integrated blower

Convenience


- Halogen lighting spotlights your best recipes
- Dishwasher safe frameless filters with stainless steel covers
- Dimmer lighting for a soft lighting effect
- Delayed shut off tackles lingering odors for up to 10 minutes
- Built-in 'Clean Filter' reminder light illuminates after 40 hours of operation
- · Blowers sold separately

Capacity

- Inline Blowers: VTI610D (600 CFM) or VTI1010D (1000 CFM)
- Remote Blowers: VTR630D (600 CFM) or VTR1030D (1000 CFM) or VTR1330E (1300 CFM)
- Remote Blower requires Roof Plate RFPLT600 for roof installations (600 CFM)
- Remote Blowers require Roof Plate RFPLT1000 for roof installations (1000/1300 CFM)
- 6" Round duct size
- · Vertical ducting direction

825225885825

HPIN48HS Professional Series 48" Island Hood



Product Features

Operating Mode: Ducted

Number of speed settings: 3-stage

Delay Shut off modes: 10 Number of lights: 4

Type of lamps used: Halogen Total power of the lamps (W): 80

Grease filter material: Washable stainless steel

Grease filter type: Multilayer cassette Clean filter reminders: Electronic

Consumption and connection features

UPC code: 825225885825 Material: Alu, Stainless steel

Watts (W): 80 Current (A): 10 Volts (V): 120 Frequency (Hz): 60 Approval certificates: ETL Power cord length (in): 51 2/16 " Power cord length (cm): 130.0 Plug type: 120V-3 prong

Overall appliance dimensions (HxWxD) (in): 30 3/8" - 41 3/8" / x 47 1/4" x

27 1/2'

Overall appliance dimensions (HxWxD) (mm): 772-1052 x 1200 x 700 Product packaging dimensions (HxWxD) (in): 22.83 x 31.88 x 46.06

Adjustable feet:

Height of the chimney (in): 28 3/8" - 39 7/16" Height of the chimney (mm): 722-1002

Vertical rise height:

Required distance above cooktop/ranges: 30"/30"

Net weight (lbs): 101 Net weight (kg): 46.000 Gross weight (lbs): 133 Gross weight (kg): 61.000

Motor location: Maximum CFM:

Diameter of air duct (in) top: 6 Diameter of air duct (in) back:

Discharge direction: No-return airflow flap: Yes

2013-07-12