


Model Name	HRD4803U
Description	Thor Kitchen 48-inch Dual Fuel Range
Gas Pipe and Regulator	
Width from Inlet Gas Pipe to Left Side of the Range (Facing from the Back)	11.5"
Height from Inlet Gas Pipe to the Ground	4.5"
Height from bottom of the Back Panel to the Ground	7.5"
Depth From Back of the Leg to the Bottom Plate	3"
Size of the Gas Inlet	1/2"
Regulator's position	At bottom right of the front oven, covered by the kick panel
Product Dimension	
Height From the Ground to the Countertop	35 1/2" - 36 1/2"
Product Dimension (W*D*H)	47 7/8" * 26" * 35 1/2"
Required Cutout Size (W*D*H)	48" * 24" - 25" * 35 1/2" - 36 1/2"
Adjustable Range Leg	1"
Circuit Breaker	40A
Picture of the Range's Back	
	

Electrical Requirements, Connection & Grounding Guidelines

**** The Plug is not included in the package. Please purchase this plug from your local appliance store. ****

This appliance is manufactured ready to be installed with a 4-wire cord set.

A 3-Pole, 4-Conductor Cord Kit with **NEMA Type 14-50R**, 50 Amperes dedicated circuit and marked for use with ranges is recommended by the manufacturer for Thor Kitchen Dual Fuel Ranges.



4-wire receptacle (14-50R)

HRD3088U and HRD3606U require a minimum of **30 Amperes** with 220 Volts;

HRD4803U requires a minimum of **40 Amperes** with 220 Volts.

We recommend A 3-Pole, 4-Conductor Cord Kit with **NEMA Type 14-50R**.