

TACR2329SSDRGX

TRUARCTIC

29 Inch Commercial Solid Door Refrigerator

23 Cu. Ft

Features

- **Consistent Commercial Cooling Performance -**
Maintains consistent cooling between 0.5°C and 5°C (33°F–40°F) with easy-to-use electronic controls.
- **Built with a 304SS interior and 430SS exterior** for durability and corrosion resistance. Features a removable access panel for easy maintenance, plus 4 casters for mobility, including 2 front locking wheels for secure placement.
- **Energy-Efficient with Long-Lasting Compressor**
Uses eco-friendly R290 refrigerant and a high-quality Embraco compressor for efficient operation and extended lifespan.

Available Colors

Stainless Steel



Specification

Brand	Truarctic	Model	TACR2329SSDRGX
Type	Commercial Reach-In Refrigerator	Installation	Freestanding
Finish	Stainless Steel	Certification	ETL Safety & Sanitation

Capcity & Storage

Capacity	650 L (23 cu. ft.)	Number of Doors	1
Shelves	3 Adjustable	Interior Material	304 Stainless Steel
Shelf Type	Heavy-Duty, Adjustable	Storage Use	Commercial Food Storage

Construction & Design

Exterior Material	430 Stainless Steel	Back Panel	Aluminum
Door Type	Swing, Self-Closing	Ice Maker	N/A
Mobility	Heavy-Duty Casters with Brakes	Door Features	Lockable, 90° Stay-Open
Reversible Door	Yes	Access Panel	Removable Service Panel
Compressor	Embraco	Interior Light	LED Lighting

TACR2329SSDRGX

TRUARCTIC

29 Inch Commercial Solid Door Refrigerator

23 Cu. Ft

Performance

Temperature Range	0.5 °C to 5 °C (33°F to 40°F)	Temperature Control	Electronic Digital
Refrigerant	R290 (Hydrocarbon, Eco-Friendly)	Cooling System	Self-Contained
Defrost	Automatic	Condenser Access	Easy Access for Cleaning
Energy Efficiency	High-Efficiency Refrigerant	Climate Impact	Lower GWP vs R134a/R404a

Electrical & Dimensions

Voltage	115 V / 60 Hz	Plug Type	NEMA 5-15P
Dimensions (W x D x H)	73.7 x 81.9 x 209.6 cm (29" x 32.25" x 82.5")	Weight	126 kg (278 lb.)