

ELEGANT AND EFFICIENT

- 3-speed high performance blower featuring 550 CFM, HVI certified*, offering 1.5 sones level at minimum speed
- Two ultra efficiency hybrid baffle filters, easy to clean, for optimal grease removal
- Two built-in LED modules provide an even lighting over the cooktop
- 3-year warranty on LED modules
- For a non-ducted installation, use recirculation kit HRKBBLS (black stainless steel) or HRKBSS (stainless steel)
- Telescopic chimney for 8' to 9' ceiling
- Optional flue extension available for 10' ceiling

SPECIFICATIONS

WIDTH	MODEL	COLOR	VOLTS	AMPS	CFM (HVI*/MAX AIRFLOW)	SONES (MIN./MAX.)	DUCTING
30"	VCS55030SSL	STAINLESS STEEL	120	3.9	550/600	1.5/11.0	3 ¼" X 10" (H-V) 6" ROUND (V)
30"	VCS55030BSL	BLACK STAINLESS STEEL	120	3.9	550/600	1.5/11.0	3 ¼" X 10" (H-V) 6" ROUND (V)
36"	VCS55036SSL	STAINLESS STEEL	120	3.9	550/600	1.5/11.0	3 ¼" X 10" (H-V) 6" ROUND (V)
36"	VCS55036BSL	BLACK STAINLESS STEEL	120	3.9	550/600	1.5/11.0	3 ¼" X 10" (H-V) 6" ROUND (V)

OPTIONS

OPTIONS	
63680	STAINLESS STEEL FLUE EXTENSION FOR 10' CEILING
63685	BLACK STAINLESS STEEL FLUE EXTENSION FOR 10' CEILING
HRKBBLS	RECIRCULATION KIT IN BLACK STAINLESS STEEL
HRKBSS	RECIRCULATION KIT IN STAINLESS STEEL
FILTERECB	CHARCOAL REPLACEMENT FILTERS FOR 30" AND 36" MODELS
ARP6	AIRFLOW REDUCER FOR 6" ROUND DUCTING (LIMITS THE AIR FLOW OF THE RANGE HOOD UNDER 300 CFM)
ARP310	AIRFLOW REDUCER FOR 3 ¼" X 10" DUCTING (LIMITS THE AIR FLOW OF THE RANGE HOOD UNDER 300 CFM)

'RANGE HOOD AIRFLOW HAS BEEN TESTED BY AN INDEPENDENT LABORATORY DESIGNATED BY THE HOME VENTILATING INSTITUTE (HVI). THE MAXIMUM AIRFLOW OF THE BLOWER IS 600 CFM.










2-LEVEL LIGHTING



TWO ULTRA EFFICIENCY HYBRID BAFFLE FILTERS



550 Lemire Blvd Drummondville (Quebec) J2C 7W9 1-800-567-3855